





Thermo Scientific Wellwash and Wellwash Versa Strip Washers

Ease of use, convenience and versatility for washing microplates in ELISA assays



# Thermo Scientific Wellwash and Wellwash Versa – Ease of use, convenience and versatility for washing microplates in ELISA assays

The Thermo Scientific Wellwash and Wellwash Versa are easy-to-use strip washers that offer convenience through a graphical user interface, eight language versions and a USB port.

The Wellwash<sup>®</sup> is the basic model for washing 96-well plates only. It is intended for use when only a few similar assays are run routinely. The Wellwash Versa is the advanced model which can also wash cells and 384-well plates, offering enhanced flexibility needed for research use.

#### **Thermo Scientific Wellwash offers**

- Easy set-up of wash protocols through a large color screen and a visual user interface
- Convenience with internal software available in eight languages: English, French, German, Spanish, Portuguese, Russian, Japanese, and Chinese
- A USB port for transferring protocols between several washers, and easily updating the internal software
- A sweep mode to guarantee an extremely low residual volume in the well, resulting in excellent washing performance and reliable assay results

## Thermo Scientific Wellwash Versa offers

- Double 2 x 8 and 2 x 12 wash heads, 1x16 wash head, and two wash bottles and one rinse bottle for increased flexibility
- Specially designed 1 x 8 and 2 x 8 wash heads enabling cell washing
- Adjustable wash parameters, such as dispense and aspiration height and the aspiration speed for optimal washing performance

#### Easy and convenient to use

The large color display makes the Thermo Scientific Wellwash and Wellwash Versa very easy and convenient to use. The user interface is logical and intuitive, requiring minimal training so that protocols can be developed quickly. A context-sensitive help feature is included in both instruments. The internal software is available in eight languages (English, French, German, Spanish, Portuguese, Russian, Japanese, and Chinese) adding more convenience of use.

Color-coded tube fittings and liquid level sensor cables enable fast instrument set-up. The removable priming vessel and built-in maintenance programs offer easy maintenance. A quick change of manifolds facilitates the use of different plate types and applications.

## Optimal washing performance for reliable assay results

The Wellwash washers efficiently remove liquid from wells. Very low residual volumes eliminate high background signal to ensure reliable assay results without the possibility of decreased assay sensitivity or false positive or negative test results.

Residual volumes are further minimized by the crosswise sweep mode. By adjusting wash parameters, such as the dispense and aspiration height, and the aspiration speed, washing performance can be optimized to guarantee that the best possible washing performance is achieved.





Wellwash

#### **Reliable and secure performance**

The wash and waste bottles in the Wellwash washers are not pressurized to minimize the risk of spillage and to prevent the washing liquid from being drawn into the aspiration pump, which could damage the instrument. For added convenience, users can substitute bottles of different sizes.

After using the instrument, the automatic rinse feature can be set to operate in a specified time sequence to ensure that the liquid channels do not get clogged. The auto-prime feature dispenses a small amount of liquid at a selected time interval.

The liquid level sensors in both the wash and waste bottles guarantee safe performance. The plate sensor recognizes if a plate is present or not. The aerosol cover prevents aerosols of infectious diseases from spreading.

## Added versatility for research use


Both washers feature linear shaking to increase washing efficiency. A USB flash memory stick transfers protocols between the PC and the washer, or several washers. It also facilitates easy update of the internal software, and downloading log files and reports.

A specially-designed wash head is available for cell washing. The wash parameters of the Wellwash Versa can be adjusted to achieve a gentle wash to remove excess liquid without disturbing the cell layer, critical for cell washing applications.

Bottle stands for the included bottles as well as a special stand for user bottles are available for added convenience. A four liter wash bottle and a nine liter waste bottle are also available for the Wellwash Versa for automation applications.

To increase assay throughput, the Wellwash Versa can be connected to automation systems such as the Thermo Scientific RapidStak microplate stacker.

## Accessories



Wellwash Versa with a USB flash memory stick

Wellwash Versa user interface - wash parameters

09.52

| <b>Technical Specificat</b> | ions  |   |
|-----------------------------|---|---|
| Feature                     | Wellwash                                    | Wellwash Versa  |
| Number of wash buffers      | 1   | Up to 3   |
| Bottles                     | 2 I wash bottle, 2 I waste bottle           | 2 x 2 I wash bottles, 1 x 2 I rinse bottle, 4 I waste bottle                            |
| Wash heads                  | 1 x 8 and 1 x 12 wash head                  | 1 x 8, 1 x 12, 2 x 8, 2 x 12, and 1 x 16 wash heads,<br>1 x 8 and 2 x 8 cell wash heads |
| Plate types                 | 96-well plates                              | 96-, 384-well plates  |
| Vash volume                 | 50-1000 μl                                  | 50-1000 µl (96), 20-300 µl (384)  |
| Prime volume                | 5 -100 ml                                   | 5 -100 ml   |
| Rinsing volume              | 5 -100 ml                                   | 5 -100 ml   |
| Dispensing volume           | 50 - 400 μl                                 | 50 - 400 µl (96), 20 - 120 µl (384)   |
| Residual volume             | < 1.5 µl                                    | < 1.5 µl  |
| Data connection             | USB port                                    | USB port  |
| Robot compatible            | No  | Yes (RS-232C)   |
| Dimensions (HxWxD)          | 345 x 385 x 240 mm<br>13.6 x 15.2 x 9.4 in. | 345 x 385 x 240 mm<br>13.6 x 15.2 x 9.4 in.   |
| Weight                      | 9 kg (20 lbs.)                              | 9 kg (20 lbs.)  |



| Ordering Info   | rmation   |                         |                          |  |
|-----------------|---|-------------------------|--------------------------|--|
| Catalog Number  | Description   |                         |                          |  |
| 5165000         | Wellwash, 100-240 V, 50/60 Hz, includes 1 x 8 wash head, 1 x 2 I wash bottle, 1 x 2 I waste bottle, aerosol cover |                         |                          |  |
| 165010          | Wellwash Versa, 100-240 V, 50/60 Hz, includes 2 x 8 wash head, 2 x 2 I wash bottle, 1 x 2 I ri                    | nse bottle, 1 x 4 l was | te bottle, aerosol cover |  |
| Vellwash Access | ries  |                         |                          |  |
| atalog Number   | Description   | Wellwash                | Wellwash Versa           |  |
| 0800            | 1 x 8 wash head   | Х                       | Х                        |  |
| 0801            | 1 x 12 wash head  | Х                       | Х                        |  |
| 0802            | 1 x 8 cell wash head, Wellwash Versa  | -                       | Х                        |  |
| 803             | 1 x 16 wash head, Wellwash Versa  | -                       | Х                        |  |
| 804             | Blank wash head, Wellwash Versa   | -                       | Х                        |  |
| )805            | 2 I wash bottle, Wellwash   | Х                       | -                        |  |
| 806             | 2 I waste bottle, Wellwash  | Х                       | -                        |  |
| 307             | 2 I wash bottle A, Wellwash Versa   | -                       | Х                        |  |
| 808             | 2 I wash bottle B, Wellwash Versa   | -                       | Х                        |  |
| 09              | 2 I rinse bottle, Wellwash Versa  | -                       | Х                        |  |
| 310             | 4 I waste bottle, square  | Х                       | Х                        |  |
| 811             | 4 I wash bottle A, round  | Х                       | Х                        |  |
| 812             | 4 I wash bottle B, round, Wellwash Versa  | -                       | Х                        |  |
| 0813            | 4 I rinse bottle, round, Wellwash Versa   | -                       | Х                        |  |
| 0814            | 9 I waste bottle, rectangular, Wellwash Versa   | -                       | Х                        |  |
| 1815            | Aerosol cover, Wellwash   | Х                       | -                        |  |
| 816             | Aerosol cover, Wellwash Versa   | -                       | Х                        |  |
| 817             | Bottle stand 1 x 2 configuration (2 x 2 l bottles), Wellwash  | Х                       | -                        |  |
| 318             | Bottle stand 2 x 2 configuration (3 x 2 l bottles, 1 x 4 l bottle, square), Wellwash Versa                        | -                       | Х                        |  |
| 819             | Bottle stand 1 x 4 configuration (3 x 2 l bottles, 1 x 4 l bottle, square), Wellwash Versa                        |                         | Х                        |  |
| )820            | Bottle stand for user bottles   | Х                       | Х                        |  |
| 0821            | Storage bottle 2 I  | Х                       | Х                        |  |

© 2010 Thermo Fisher Scientific Inc. All rights reserved. Windows and Vista are registered trademarks of Microsoft Corporation. IBM is a registered trademark of International Business Machines Corporation. All other trademarks are the property of Thermo Fisher Scientific Inc. and its subsidiaries. Specifications, terms and pricing are subject to change. Not all products are available in all countries. Please consult your local sales representative for details.

North America: USA/Canada 800 345 0206 Europe: Austria +43 1 801 40 0, Belgium +32 53 73 42 41, France +33 2 2803 2180, Germany national toll free 08001-536 376, Germany international +49 6184 90 6940, Italy +39 02 02 95059 448, Netherlands +31 76 571 4440, Nordic/Baltic countries +358 9 329 100, Russia/CIS +7 (495) 739 76 41, Spain/Portugal +34 93 223 09 18, Switzerland +41 44 454 12 12, UK/Ireland +44 870 609 9203 Asia: China +86 21 6865 4588 or +86 10 8419 3588, India toll free 1800 22 8374, India +91 22 6716 2200, Japan +81 45 453 9220, Other Asian countries +852 2885 4613 Countries not listed: +49 6184 90 6940 or +33 2 2803 2180

Storage bottle 4 I, round

N10822

www.thermoscientific.com www.thermoscientific.com/wellwash

